


# PROFIVE® NUCE\_C 54W

## APPLICATIONS

The **PROFIVE® NUCE** was designed as a low power eNUC board with an excellent performance-per-watt ratio and is optimal adapted for:

- \_ AI Systems
- \_ Medical Solutions
  - AMD Ryzen™ performance
- \_ ML Machine Learning
- \_ CV Computer Vision
- \_ Robotics
- \_ Micro-Server
- \_ High-Performance Workstations
- \_ Industrial Systems
  - low power | high performance
- \_ IoT
  - edge / fog gateway

<sup>1</sup>10 years availability according to CPU manufacturers specification



HIGH QUALITY  
MADE IN GERMANY

AMD  
RYZEN  
Embedded

 10 years  
long life  
support <sup>1</sup>


E.E.P.D.   
...just embedded!

# eNUC 101x101

## SPECIFICATIONS

CPU	AMD V2000 series <sup>1</sup> up to 4.25 GHz, up to 8 cores, 16 threads, max. 54W supported
Max. memory	Up to 64 GB dual channel DDR4-3200 SO-DIMM memory with support for ECC-RAM modules
Gigabit Ethernet	2 Intel® I225 with 2,5 Gbit/s and IEEE1588 TSN-support   Wake-On-LAN supported by one port
M.2 socket	1 Key B, 30 mm x 42 mm 1 Key E, 22 mm x 30 mm 1 Key M, 22 mm x 42 mm (SATA or NVMe with PCIe4)
USB ports	1 Dual USB 3.1 Gen2 (10Gb/s, limited to: 1.5A each) 2 internal USB 2.0 (limited to: 900mA each)
USB-C connector	1 USB-C 3.1 Gen2 or ALT-Mode support (10Gb/s, limited to: 3A)
DP connectors	2 Mini-DP++ connectors up to 4096 x 2160 @ 60 Hz
Serial port	2 RS-232/485 (HDX/FDX) provided through SUPER I/O
Sound	HDA with MIC in / Headphone out at a 3.5 mm Audio Jack / Line in / Line out
fTPM / TPM	AMD firmware Trusted Platform TPM 2.0 support (Infineon SLB 9670)
Health monitoring and management	Controllable FAN (PWM + Tacho) Hardware monitoring and watchdog
Other	Power and status LEDs, max. 4 GPIO (3.3V) and max. 3 GPO with PWM (3.3V/50kHz)
Power supply	Min. 10.8 V / Max. 26.4 V (DC)
Max. operating temp.	0°C to +60° ambient commercial grade; other on request
Max. storage temp.	-40°C to +85°C
Max. relative humidity	95% @ 40°C, non-condensing
Size approx.	139 x 86 x 110mm
Weight approx.	890g + options
OS support	Microsoft® Windows® 11 Microsoft® Windows® 10 Microsoft® Windows® 10 IoT Enterprise Linux Ubuntu 22.04 LTS


Ordering code	Description	Type / Size
NUCEHCO	eNUC	V2546   6C   12T   3.0 GHz - 3.95 GHz   35 - 54W
NUCEICO	eNUC	V2748   8C   16T   2.9 GHz - 4.25 GHz   35 - 54W
4GB-NUCE_C   4GB-NUCEE_C	Main Memory	4GB
8GB-NUCE_C   8GB-NUCEE_C	Main Memory	8GB
16GB-NUCE_C   16GB-NUCEE_C	Main Memory	16GB
32GB-NUCE_C   32GB-NUCEE_C	Main Memory	32GB



**Dual-Mini-DP-Support**  
**Single Display Max. 4096 x 2160 @ 60 Hz**



**Dual 2.5 Gigabit Ethernet**



**Triple M.2 Sockets / WLAN\_BT / 4G\_5G**

The information contained in this document has been carefully checked and is believed to be reliable. However, E.E.P.D. GmbH makes no guarantee or warranty concerning the accuracy of said information and shall not be responsible for any loss or damage of what ever nature resulting from the use of, or reliance upon, it. E.E.P.D. does not guarantee that the use of any information contained herein will not infringe upon the patent, trademark, copyright or other rights of third parties, and no patent or other license is implied hereby. AMD and the AMD logo are trademarks of Advanced Micro Devices, Inc. Intel and the Intel logo are trademarks of Intel Corporation or its subsidiaries in the U.S. and/or other countries.

This document does not in any way extend E.E.P.D.'s warranty on any product beyond that set forth in its standard terms and conditions of sale. E.E.P.D. reserves the right to make changes in the products or specifications, or both, presented in this publication at any time and without notice.

LIFE SUPPORT APPLICATIONS

E.E.P.D.'s products are not intended for use as critical components in life support appliances, devices or systems in which the failure of a E.E.P.D. product to perform could be expected to result in personal injury. All mentioned trademarks are registered trademarks of their owner.

©2023 by E.E.P.D. GmbH. All rights reserved. November 13 2024 - Version 2.1 / Rev5

**E.E.P.D. Electronic Equipment  
Produktion & Distribution GmbH**

Gewerbering 3

85258 Weichs - Germany

Phone +49 8136 2282-0

Fax +49 8136 2282-109

Internet: [www.eepd.de](http://www.eepd.de)

E-Mail: [sales@eepd.de](mailto:sales@eepd.de)