



BOXPC-NUCV

EM TRUST
systems you can trust

APPLICATIONS

The **EM BoxPC-NUCV** is the perfect intelligent IoT edge node. It is a german engineered and produced high quality BoxPC System. It is optimal adapted for:

- _ AI Systems
- _ ML Machine Learning
- _ CV Computer Vision
- _ Robotics
- _ Medical Solutions
 - AMD Ryzen™ performance
- _ Mobile Systems
 - automotive power supply
- _ Rugged Industrial Systems
 - no rotating parts, low power
- _ IoT
 - edge / fog gateway

¹10 years availability according to CPU manufacturers specification
²The NUCV supports only max. 35W TDP settings

eNUC



With a large number of interfaces in a small package, a wide range of applications are supported.



A customized frontpanel design is optional available.



The BoxPC is designed for industrial-grade communication applications in extreme temperature environments.



BoxPC system with high computer performance and small dimensions.



Expand your system with various USB options.



Simultaneous use of UMTS and WLAN for extended router applications.

HIGH QUALITY
MADE IN GERMANY

 **10 years long life support¹**

 **12/24 V**

E.E.P.D. 
...just embedded!

SPECIFICATIONS

| | |
|--------------------------------------|--|
| CPU | AMD V1000 series ¹ , up to 3.8 GHz Up to 4 cores, 8 threads max. 35 W supported |
| Max. memory | 32 GB dual channel DDR4 memory |
| Gigabit Ethernet | 2 Intel® I210 with IEEE1588 |
| LTE/4G (OPTIONAL) | 300 Mbps max./EMEA, APAC/Diversity/ GNSS |
| WiFi/BT (OPTIONAL) | 802.11 AC with diversity/ Bluetooth Version 5 |
| SSD (OPTIONAL) | M.2 SATA or NVMe / 64 - 512 GB |
| SD-Card | 1 MicroSD-Card socket |
| USB ports | 1 Dual USB 3.1 Gen2 (10Gb/s, limited by fuse protection to: 900mA each) 1 Rear USB 3.1 Gen2 (10Gb/s, limited by fuse protection to: 900mA) 1 internal USB 3.1 Gen2 (10Gb/s, limited by fuse protection to: 900mA) |
| Serial ports (OPTIONAL) | 1 RS-232 1 RS-232/485 (FDX) |
| DP connectors | 2 Mini-DP++ connectors up to 4096 x 2160 @ 60 Hz |
| Sound (OPTIONAL) | 3.5 mm MIC In / headphone Out |
| Health monitoring and management | Controllable FAN (PWM + Tacho), hardware monitoring and Watchdog |
| fTPM | AMD firmware Trusted Platform Module |
| Other | Power and status LEDs |
| Power supply | Min. 8 V / Max. 32 V (DC) automotive grade KL15/terminal 15 |
| Max. operating temp. | 0°C to +60°C ambient commercial grade; other on request V1807 deviating 0°C to +50°C |
| Max. storage temp. | -40°C to +85°C |
| Max. relative humidity | 95 % @ 40°C, non-condensing |
| Housing | Sturdy metal case |
| Mounting | Stand alone or hat rail |
| Dimensions approx. | 120 x 117 x 47 mm |
| Weight approx. | 700 g + options |
| Conformity | CE, ROHS, REACH |
| OS support OS license is optional | Microsoft® Windows® 10; Microsoft® Windows® 10 IoT Enterprise; Linux Ubuntu 20.04 LTS |

VERSATILE COMMUNICATION BY A LARGE NUMBER OF INTERFACES



OVERVIEW

The BoxPC-NUCV is the perfect industrial grade communicator for secure and reliable IoT communication. It is designed as a flexible low power system with an excellent performance-per-watt ratio.

SUMMARY

- ▶ AI performance level
- ▶ Flexible communication
- ▶ OEM/ODM with customer branding in small quantities available
- ▶ Easy mounting
- ▶ High performance
- ▶ Small dimensions

| Ordering Code System | Description | Type |
|----------------------|-------------|--|
| BPCNVA (OEM only) | eNUC System | V1202B / 2C / 4T / 2.3 GHz - 3.2 GHz / 12 - 25 W |
| BPCNVB | eNUC System | V1605B / 4C / 8T / 2.0 GHz - 3.6 GHz / 12 - 25 W |
| BPCNVC (OEM only) | eNUC System | V1756B / 4C / 8T / 3.25 GHz - 3.6 GHz / 35 - 54 W ² |
| BPCNVD | eNUC System | V1807B / 4C / 8T / 3.35 GHz - 3.8 GHz / 35 - 54 W ² |
| 4GB-NUCV | Main Memory | 4 GB |
| 8GB-NUCV | Main Memory | 8 GB |
| 16GB-NUCV | Main Memory | 16 GB |

| OPTION | Description |
|--------|---------------------------------------|
| SSA | SATA SSD 64 - 512 GB |
| SSN | NVMe SSD 64 - 512 GB |
| LTE | LTE/4G Modem |
| WBT | WiFi/BT card |
| CM1 | COM 1 RS-232 Port |
| CM2 | COM 2 RS-232/485 Port |
| SND | 3.5 mm / MIC IN / Headphone OUT |
| W10 | Microsoft® Windows® 10 |
| WIE | Microsoft® Windows® 10 IoT Enterprise |
| LNx | Linux Ubuntu 20.04 LTS |

The information contained in this document has been carefully checked and is believed to be reliable. However, E.E.P.D. GmbH makes no guarantee or warranty concerning the accuracy of said information and shall not be responsible for any loss or damage of what ever nature resulting from the use of, or reliance upon, it. E.E.P.D. does not guarantee that the use of any information contained herein will not infringe upon the patent, trademark, copyright or other rights of third parties, and no patent or other license is implied hereby. AMD and the AMD logo are trademarks of Advanced Micro Devices, Inc. Intel and the Intel logo are trademarks of Intel Corporation or its subsidiaries in the U.S. and/or other countries.

This document does not in any way extend E.E.P.D.'s warranty on any product beyond that set forth in its standard terms and conditions of sale. E.E.P.D. reserves the right to make changes in the products or specifications, or both, presented in this publication at any time and without notice.

LIFE SUPPORT APPLICATIONS: E.E.P.D.'s products are not intended for use as critical components in life support appliances, devices or systems in which the failure of a E.E.P.D. product to perform could be expected to result in personal injury. All mentioned trademarks are registered trademarks of their owner.

© 2024 by E.E.P.D. GmbH. All rights reserved. November 19 2024 – Version 1.9



E.E.P.D. Electronic Equipment Produktion & Distribution GmbH

Gewerberg 3
85258 Weichs - Germany
Phone +49 8136 2282-0
Fax +49 8136 2282-109
Internet: www.eepd.de
E-Mail: sales@eepd.de