

EM PRO midi cube

the ultra-Power-Workstation

E.E.P.D. 
...just embedded!

Why EM PRO midi cube?

AMD **Ryzen™ Embedded 8000** series with ultra-efficient „Zen 4” x86 core architecture and powerful AMD RDNA3 Radeon™ Graphics and XDNA Neural Processing Unit for AI Inferencing | max. 8 cores / 16 threads



Ideal for use in:

- Video editing & photo editing
- 3D applications, animation, architectural and product design software
- 2D animation, graphics, illustrator, photography, web design software
- Construction software (e.g. CAD, CAM, electronic design, PCB design)
- Graphic design, product design, game design
- Programming workstations
- Augmented & Virtual Reality

and much more

Ultra-compact, highly efficient and extremely quiet

Design and production
Made in Germany

24/7 operation

4 x up to 4K/60Hz monitors supported with mini DP, DP, USB-C-DP Alt Mode and HDMI with adapter

AMD 
RYZEN
Embedded

CPU

AMD Ryzen™ Embedded 8845HS, 8645HS, 8840U, 8640U
up to 5.1 GHz, up to 8 cores, 16 threads,
max. 54 W supported

Max. memory

64 GB dual channel DDR5 memory
with ECC support

Housing

Sturdy aluminum Housing,
black anodized

Kensington Lock**Mounting**

Stand alone

Dimensions approx.

148 x 110 x 116 mm

Weight approx.

1.150 grams + options

Conformity

CE, ROHS, REACH

OS support

(OS licence is optional)

Microsoft® Windows® 11
Linux Ubuntu 22.04 LTS

Specification



Rear connections

Display-Port connectors

2 Mini Display Port up to 4096 x 2160 @ 60 Hz
2 USB-C-DP Alt Mode connectors up to
4096 x 2160 @ 60 Hz (secondary monitor only)

Sound

3.5 mm MIC in / headphone out

Health monitoring and management

Speed-controlled fan (PWM + Tacho)
and hardware monitoring

fTPM + TPM

AMD firmware Trusted Platform Module
Infineon SLB9670 TPM 2.0

Other

Power and status LEDs
Temperature dependent LED for indication of
system heat

Power supply

Min. 10.8 V / Max. 26.4 V (DC)

Operating temperature

0 °C to +50 °C commercial grade
- other on request

Storage temperature

-40 °C to +85 °C, non-condensing

Max. relative humidity

95% @ 40 °C, non-condensing while stored
| 89% while working

USB ports

2 USB 3.2 Gen2 (10 Gb/s,
OCP = 1500 mA each)

2 USB-C 3.2 Gen2 or
USB-C-DP Alt Mode (10 Gb/s,
OCP = 3000 mA)

Serial ports

2 RS-232/485 (HDX/FDX)

Gigabit Ethernet

2 Intel® I226-LM / 2.5 Gigabit

WiFi 6 (optional)

802.11 AX

SSD (optional)

1x M.2 NVME / PCIe 4.0 x2 / 2242
1x M.2 NVME / PCIe 4.0 x4 / 2280

E.E.P.D. Electronic Equipment
Produktion & Distribution GmbH

Gewerbering 3

85258 Weichs - Germany

Phone +49 8136 2282-0

Fax +49 8136 2282-109

Internet: www.eepd.de

E-Mail: sales@eepd.de

The information contained in this document has been carefully checked and is believed to be reliable. However, E.E.P.D. GmbH makes no guarantee or warranty concerning the accuracy of said information and shall not be responsible for any loss or damage of what ever nature resulting from the use of, or reliance upon, it. E.E.P.D. does not guarantee that the use of any information contained herein will not infringe upon the patent, trademark, copyright or other rights of third parties, and no patent or other license is implied hereby. AMD and the AMD logo are trademarks of Advanced Micro Devices, Inc. Intel and the Intel logo are trademarks of Intel Corporation or its subsidiaries in the U.S. and/or other countries. This document does not in any way extend E.E.P.D.'s warranty on any product beyond that set forth in its standard terms and conditions of sale. E.E.P.D. reserves the right to make changes in the products or specifications, or both, presented in this publication at any time and without notice. LIFE SUPPORT APPLICATIONS: E.E.P.D.'s products are not intended for use as critical components in life support appliances, devices or systems in which the failure of a E.E.P.D. product to perform could be expected to result in personal injury. All mentioned trademarks are registered trademarks of their owner.
© 2024 by E.E.P.D. GmbH. All rights reserved. April 05 2024 – Version 0.0

HIGH QUALITY
MADE IN GERMANY