

## APPLICATIONS

The P10 COM Express® was designed as value-priced entry level board, powered by the latest VIA technology. By contrast with many other COM Express® boards the P10 is below low power.

The P10 COM Express® finds his field of work in stationary and mobil devices like

- Rugged Industrial Systems
- Medical Solutions
- Automatic Control Panels
- Information Systems
- Measurement & Quality Control
- Realtime Flow Control



## P10 COM Express® Compact

**COM**   
**Express®**



- ▶ Powered by latest VIA C7®, Eden® or Nano™ processors to fit every requirement
- ▶ Full PCI Express® and PCI™ compatible CPU module with up to 800 MHz FSB
- ▶ Supports up to 4 GB DDR2 memory
- ▶ Enables analog VGA and 24-bit dual channel LVDS

- ▶ VIA VX800 ALL-IN-ONE system chipset
- ▶ PCI Express® ports (x4 / x1) and a 32-bit PCI™ interface are supported
- ▶ Two Serial ATA, one Parallel ATA and six USB 2.0 ports on board available
- ▶ Gigabit Ethernet, SM, I<sup>2</sup>C and LPC bus for communication and control

The information contained in this document has been carefully checked and is believed to be reliable. However, E.E.P.D. GmbH makes no guarantee or warranty concerning the accuracy of said information and shall not be responsible for any loss or damage of what ever nature resulting from the use of, or reliance upon, it. E.E.P.D. does not guarantee that the use of any information contained herein will not infringe upon the patent, trademark, copyright or other rights of third parties, and no patent or other license is implied hereby.

Intel and Intel logo are trademarks or registered trademarks of Intel Corporation or its subsidiaries in the United States and other countries.

This document does not in any way extend E.E.P.D.'s warranty on any product beyond that set forth in its standard terms and conditions of sale. E.E.P.D. reserves the right to make changes in the products or specifications, or both, presented in this publication at any time and without notice.

**LIFE SUPPORT APPLICATIONS**

E.E.P.D.'s products are not intended for use as critical components in life support appliances, devices or systems in which the failure of a E.E.P.D. product to perform could be expected to result in personal injury.

All mentioned trademarks are registered trademarks of their owner.

© 2014 by E.E.P.D. GmbH. All rights reserved.

February 2014 - Version 1a

# P10 COM Express® Compact

CPU	VIA Eden® processor 500 MHz / 128 KB cache / 400 MHz FSB / 1 Watt VIA C7® processor 1.5 GHz / 128 KB cache / 400 MHz FSB / 12 Watt VIA Nano™ processor on request Up to 800MHz FSB
Chipset	VIA VX800 ALL-IN-ONE system chipset
Type	COM Express® Compact module
COM Express® pin out Type 2	
BIOS	SPI flash BIOS External BIOS ROM support
Max. memory	Up to 4 GB DDR2 supports 400 MHz, 533 MHz or 667 MHz
PCI Express® lanes	Two ports (x4 and x1)
32-bit PCI™ bus	Yes
Serial ATA ports	2
Parallel ATA port	1
Gigabit Ethernet	Yes
LPC interface	Yes
SM bus	Yes
I²C bus	Yes
USB 2.0 ports	6
Analog VGA	Yes
LVDS interface	Yes, 24-bit dual channel LVDS
DVI-I / TV OUT	Optional, on base board via Digital Video Port
Sound	High Definition Audio support
Health monitoring and management	Thermal protection and Watchdog
Size approx.	95 x 95 mm

