



The information contained in this document has been carefully checked and is believed to be reliable. However, E.E.P.D. GmbH makes no guarantee or warranty concerning the accuracy of said information and shall not be responsible for any loss or damage of what ever nature resulting from the use of, or reliance upon, it. E.E.P.D. does not guarantee that the use of any information contained herein will not infringe upon the patent, trademark, copyright or other rights of third parties, and no patent or other license is implied hereby.

Intel and Intel logo are trademarks or registered trademarks of Intel Corporation or its subsidiaries in the United States and other countries.

This document does not in any way extend E.E.P.D.'s warranty on any product beyond that set forth in its standard terms and conditions of sale. E.E.P.D. reserves the right to make changes in the products or specifications, or both, presented in this publication at any time and without notice.

#### LIFE SUPPORT APPLICATIONS

E.E.P.D.'s products are not intended for use as critical components in life support appliances, devices or systems in which the failure of a E.E.P.D. product to perform could be expected to result in personal injury.

All mentioned trademarks are registered trademarks of their owner.

© 2014 by E.E.P.D. GmbH. All rights reserved.

February 2014 - Version 1a

# P14 COM Express®

CPU for industrial temperature grade	Intel® Atom™ processor Z520PT / 1.33 GHz / 512 KB cache / 533 MHz FSB Z510PT / 1.1 GHz / 512 KB cache / 400 MHz FSB
CPU for standard temperature grade	Intel® Atom™ processor Z530P / 1.6 GHz / 512 KB cache / 533 MHz FSB Z510P / 1.1 GHz / 512 KB cache / 400 MHz FSB
Chipset for industrial temperature grade	Intel® System Controller Hub US15WPT with FSB supports 400 MHz and 533 MHz
Chipset for standard temperature grade	Intel® System Controller Hub US15WP with FSB supports 400 MHz and 533 MHz
COM Express® pin out	Type 2 version
Max. memory	Up to 2 GB DDR2 memory support
PCI Express® lanes	Up to 4 PCI Express® lanes
32-bit PCI™ bus	Yes
Serial ATA interfaces	2 (Option)
Parallel ATA interface	1
Solid State Drive	Up to 4 GB (Option)
Gigabit Ethernet	Yes
SM / LPC bus	Yes
USB ports	Up to 8 (1 client port optional)
Analog VGA interface	Yes (Option, shared with SDVO interface)
LVDS interface	Yes, 24-bit single channel LVDS
Serial DVO interface	Yes, shared with VGA interface
Sound	HDA interface
Max. operating temperature	-40°C to +85°C ambient industrial grade 0°C to +60°C ambient standard grade
Type	COM Express® Compact module
Size approx.	95 mm x 95 mm

